

Mini Portable Hot Water System

P/N AAI-MP-800-A



Features:

- Digital Controlled Process Temperature 1 + or - 1°F
- Fuel System Digital Control
- Cathodic Protected – AAI Anode Assemblies
- Mechanical Temperature Probe
- Stainless Steel Pump
- Primary Cartridge Fuel Filter
- AAI Flow Mixing Temperature Stabilizer Assembly
- G.F.C.I. Protected
- No Mixing Valves
- Digital Control Microprocessor
- Electrical Requirements: 115V 60Hz, Single Phase, 16.4 Amps

	Mini Portable
	Roll-Around Cart w/ Pneumatic Wheels & Stainless Steel Cover
Heater Output	350,000 BTU
Output	6 gal/min – 120 psi
Fuel Tank – Urethane or Aluminum	8 gal
Length	40"
Width	19"
Height	32"
Dry Weight	150 lbs.
Standard Package	Mixing Tank, Water Filter, S.S. Pump

All AAI Hot Water Units Equipped with: “5 way Protection System”

- Digital Control Temperature Probe – High Temperature Alarm Option
- Magnetic Flow Control Sensor
- Primary Fuel Solenoid Valve
- Diver’s Water Mixing Tank
- AAI Water Filter Assembly – 100 Micron