

AAI TURBO SCRUBBER

Part No. AAI-1300-A1



When using the Turbo Scrubber, the chamber atmosphere will have a constant circulation of Air-CO₂, Water Vapor, & Odor Absorption. The unit can be powered by an AC/DC power supply (not included) or by a 24 volt back up battery for up to 24 hrs of operation.

The stainless steel canister of the Turbo Scrubber can be configured with proper chemicals to maintain CO₂, water vapor, & odor levels generated within a chamber.

Features:

- Installed Weight Empty - 18 lbs.
- Installed Weight Filled with Absorbent – 25.5 lbs.
- Power Requirements - 1.5 AMPS 24V AC OR DC
- CO₂ Absorbent - (SOFNOLIME) 7.5 lbs.
- Flow Rate- 30 cfm (actual)
- Rugged Stainless Steel built-in mounting bracket
- Dimensions 15” L x 10” W x 8” H
- 6 Person capacity per Turbo Scrubber unit

The stainless steel Turbo Scrubber is powered by 110/24 volt “magnetic coupled” dual fans which move 30 cubic feet per minute through the scrubber canister. The fan motors are designed to work in high levels of oxygen without electrical sparks.

Turbo Scrubber Assy. Complete with Built-In Mountng Bracket –Order P/N ..AAI-1300-A1
Power Supply – Order P/N.....AS320-24